NetaCap

An advanced multi-depth soil moisture and temperature sensor that provides valuable insights to improve both irrigation planning and strategic decision-making.









AAA AAA AAA

Open field

/ Highlights & Benefits

- → High accuracy and reliability
- → Cost-efficient, high-level instrument
- \rightarrow Easy installation
- ightarrow Ideal for all root zones with any soil type
- ightarrow Additional ambient temperature measurement on top of the probe

['] Technical Specifications

- Air temperature sensor
 Soil moisture sensors
- Soil temperature sensor
- Equipment Type Electronic probe based on capacitance technology (FDR)
- Soil Moisture Range 0-100% Soil moisture probe (0- 50% VWC)
- Soil Temperature Range -15°C to 64°C (5°F to 147.2°F)
- Influence of Salinity Less than 1% over the standard operating range
- Available Lengths 20, 30, 40, 60, 80, 120cm (8", 12", 16", 24", 32", 47")
- Body Material UV stabilized PVC (polyvinyl chloride) plastic
- Communication RS232
- **Power Source** 3.6V DC, 50mA
- Cable Length Model WP: 5m (16.4ft), extendable up to 25m (82ft) / Model BP: 3m (9.84ft)
- **Protection** IP68 (Excluding cable end)



Want to know more? products_solutions@netafim.com



ightarrow Sensor Location Along the Probe

	Probe Length					
Sensor Depth	Bag Probe		Wire Probe			
	20cm (7.8")	30cm (11.8")	40cm (15.7")	60cm (23.6")	80cm (31.5")	120cm (47.2")
10cm (3.9")	I	Ø	I	Ø		
20cm (7.8")	v	Ø	v	v	Ø	Ø
30cm (11.8")		Ø	I	Ø	Ø	
40cm (15.7")			O	O	Ø	
50cm (19.6")						
60cm (23.6")				O	Ø	
70cm (27.5")						
80cm (31.5")					Ø	Ø
90cm (35.4")						
100cm (39.3")						Ø
110cm (43.4")						
120cm (47.2")						v

*Bag probes are probes without the extended cap, meaning they can be fully submerged in the substrate. They are often used in soilless media in greenhouses, inserted either vertically or horizontally.

\rightarrow Wiring Diagram				
Terminal	Wire			
+	- Yellow			
Rx	⊖ White			
Tx	Green			
-	Brown			

\rightarrow Installation

- 1. Select the optimal location of the probe that represents the average condition of the crop in the plot
- 2. The sensor should be located around 10 15cm from the dripper, within the wetted bulb and the active root zone

\rightarrow Care & Maintenance

After use, store the probe in a controlled environment with temperatures between 0 to 45 degrees celsius and relative humidity ranging from 0 to 90 percent. Do not store in direct sunlight

\rightarrow Kit Contents

- NetaCap sensor
- Product sheet

\rightarrow Catalog Numbers

Description	Catalog Number
SOIL MOISTURE NETACAP BP 2/20CM	74730-000007
SOIL MOISTURE NETACAP BP 3/30CM	74730-000013
SOIL MOISTURE NETACAP WP 4/40CM	74730-000008
SOIL MOISTURE NETACAP WP 6/60CM	74730-000009
SOIL MOISTURE NETACAP WP 6/80CM	74730-000011
SOIL MOISTURE NETACAP WP 6/120CM	74730-000021



